Amendments to the Claims

Please amend claims 2, 3, 7, 8, 10, 11, 14, and 15; and add new claims 18-23. The following listing of claims replaces all prior versions and listings of claims in the present invention:

1. (Original) An illumination device comprising:

a substrate having a surface and a cavity in the surface;

at least one light emitting diode (LED) mounted within the cavity;

a phosphor monolayer comprising phosphor particles overlying the LED, the phosphor particles for converting the emitted light into white light, the phosphor monolayer adhered to the LED by a monolayer of adhesive material.

- 2. (Currently Amended) The illumination device of claim 1 further comprising overlying the phosphor monolayer, a thick layer of transparent material encapsulating the LED and optionally to form a lens for the LED.
- 3. (Currently Amended) The illumination device of claim 1 wherein the substrate comprises a heat sink and the LED is thermally coupled to the heatsink heat sink.
- 4. (Original) The illumination device of claim 1 wherein the LED is a blue or ultraviolet LED.
- 5. (Original) The illumination device of claim 1 wherein the phosphor monolayer is a monolayer of phosphor particles.
- 6. (Original) The illumination device of claim 1 wherein the phosphor comprises a YAG:Ce phosphor.
- 7. (Currently Amended) A method for making an illumination device comprising one or more white light LEDs emitting diodes (LEDs) comprising the steps of:

providing a workpiece comprising a substrate having a surface including one or more cavities that contain one or more LEDs connected to electrical leads;

forming a coating of tacky adhesive material overlying at least one of the LEDs;
exposing the coating of tacky material to particles comprising phosphor material
to form a self-limiting coating of particles overlying the at least one LED; and
curing the tacky adhesive material.

- 8. (Currently Amended) The method of claim 7 further comprising the steps of applying an optical material in the cavity to encapsulate the coated LED-and optionally to form a lens for the LED.
- 9. (Original) The method of claim 7 wherein the substrate comprises a heat sink and the LED is thermally coupled to the heat sink.
- 10. (Currently Amended) The method of claim 7 wherein at least one of the LEDs is a blue or <u>ultraviolet</u> [[UV]] LED.
- 11. (Currently Amended) The method of claim 7 wherein the coating of tacky adhesive material comprises a monolayer of tacky adhesive material.
- 12. (Original) The method of claim 7 wherein the coating of particles comprises a monolayer of particles.
- 13. (Original) The method of claim 7 wherein the tacky adhesive material is cured by heating.
- 14. (Currently Amended) The method of claim 7 8 wherein the optical material applied to encapsulate the LED is applied by syringe injection or by injection molding.
- 15. (Currently Amended) The method of claim 7 further comprising the step of dicing the workpiece into a plurality of white <u>light</u> LED devices.
 - 16. (Original) The method of claim 7 further comprising the step of masking portions

of the workpiece prior to coating with tacky adhesive.

17. (Original) Apparatus for coating phosphor particles on adhesive-coated LED workpieces comprising:

an enclosed particle coating chamber for receiving the workpieces,

a reservoir of phosphor particles to be coated, coupled to the chamber;

a source of pressurized gas coupled to the chamber through a Venturi Nozzle; and
a recycling chamber for receiving and recycling unused particles coupled to the chamber.

- 18. (New) An illumination device comprising:
 - a substrate having a cavity;
 - at least one light emitting diode (LED) mounted within the cavity;
 - a tacky material overlying the at least one LED; and
 - a layer comprising phosphor particles adhered to the LED by the tacky material.
- 19. (New) The illumination device according to claim 18 further comprising an encapsulant overlying the layer comprising phosphor particles.
- 20. (New) The illumination device according to claim 18, wherein the substrate comprises a heat sink and the at least one LED is thermally coupled to the heat sink.
- 21. (New) The illumination device according to claim 18, wherein the at least one LED comprises a blue LED.
- 22. (New) The illumination device according to claim 18, wherein the at least one LED comprises an ultraviolet LED.

23. (New) The illumination device according to claim 18, wherein the phosphor particles comprise YAG:Ce.